NBS-E 1600/3L 1600A 3P

Specifikace

Kód ETI	004673163
Popis	NBS-E 1600/3L 1600A 3P
Jmenovitý proud (A)	1600
Počet pólů	3
Normy	60947
Typ připojení	přední připojení
Jmenovité impulsní výdržné napětí (kV)	8
Jmenovité pracovní napětí (V AC)	690
Jmenovité izolační napětí (V)	1000
Jmenovitá zkratová schopnost při 415V Icu/Ics (kA)	36
Tepelné nastavení	0,4-1
Magnetické nastavení	1,5-10xIr
Nastavitelné nebo pevné	nastavitelný

Online stránka produktu

Další dokumentace

3D model
Návod
Prohlášení CE
Eplan file

Mezinárodní klasifikace ETIM

Klasifikace	EC000228
Název třídy	Power circuit-breaker for trafo/generator/installation protection
Rated permanent current Iu	1600A
Rated voltage	415...690V
Rated short-circuit breaking capacity Icu at 400 V, 50 Hz	36kA
Overload release current setting	640...1600A
Adjustment range short-term delayed short-circuit release	960...16000A
Integrated earth fault protection	
Type of electrical connection of main circuit	Screw connection
Device construction	Complete device in housing
Suitable for DIN rail (top hat rail) mounting	
DIN rail (top hat rail) mounting optional	
With switched-off indicator	1
With under voltage release	
Number of poles	3
Position of connection for main current circuit	Front side
Type of control element	Toggle
Complete device with protection unit	1
Motor drive integrated	
Motor drive optional	1
Degree of protection (IP)	IP20